


SPECIFICATIONS



Overall length	10,34 m / 33'11"
Overall Length with Bowsprit	10,69 m / 35'
Hull length	9,97 m / 32'8"
Waterline length	9,40 m / 30'10"
Beam	3,44 m / 11'3"
Displacement light load with deep draft keel	5340 kg / 11773 lbs
Standard keel draft	1,98 m / 6'5"
Standard keel weight	1580 kg / 3483 lbs
Shoal keel draft	1,49 m / 4'10"
Shoal keel weight	1860 kg / 4101 lbs
Lifting keel draft	1,26-2,54 m / 4'1"-8'4"

Lifting keel weight	1532 kg / 3377 lbs
CE category	A6 / B8
Fuel capacity	130 L / 34 US gal
Water capacity	206 L / 54 US gal
Fridge capacity	100 L / 26 US gal
Holding tank capacity	80 L / 21 US gal
Architect/Designer	Marc Lombard / Jeanneau Design
Standard mainsail horizontally-cut in high-quality dacron	30,70 m² / 330 Sq ft
Standard headsail 110% horizontally-cut in high-quality dacron	24,60 m ² / 265 Sq ft

AN EXCEPTIONAL LEVEL OF EQUIPMENT

EXTERIOR

Sailing features

- High aspect ratio rig
- Harken deck hardware
- Aluminium classic mast
- Semi full-batten main and furling genoa with UV protection
- Standing rigging discontinuous stainless steel wire
- Sheets lead back to the helm German sheeting
- Double rudders

Construction

- Hull solid, hand-laid fibreglass, ISO gelcoat surface, protective barrier coat
- Deck Prisma Process® injected deck, ISO gelcoat surface, discontinuous balsa block coring – 30% weight savings as compared to traditional decks

Woodwork

- Woodwork in Alpi teak
- UV stabilised varnish
- Light oak laminate floorboards
- Numerous solid wood mouldings

Cockpit

- One-level cockpit with dedicated sail handling areas
- Twin helms
- Multi-function cockpit table (option)
- Leather-covered steering wheels
- Fold down swim platform with telescopic swim ladder (option)

Deck

- Flush deck hatches
- Long acrylic deck windows
- Stainless steel handrails on the coachroof
- Mooring cleats
- Electric windlass (option)

INTERIOR

- One-level interior with no door sills
- Leather-wrapped handrails
- Direct and indirect LED lighting
- Large, double berths
- Fully-upholstered hull sides and ceiling
- Large storage spaces, seaworthy with fiddles

Gallev

- Laminated slate countertops
- Stainless steel sink
- Gimballed 2-burner stove with protective handrail
- Fridge 100L / 26 US Gal with top access to better maintain the cold air
- Freezer compartment

TECHNICAL

Electrical

- 12V electrical panel
- Battery Exide Dual Marine
- 125A alternator and charge distributor/isolator
- Positive and negative battery cut-off switches to better protect battery banks

Water systems

- "Heavy-duty" water pump
- Chromed faucets
- Holding tank with gravity drain and deck fitting

Engine

- Fixed 3-blade propeller
- Sound insulation 40 mm / 1 1/2" thick

TRIM LEVELS AND PACKAGE

	PREMIERE	PREFERENCE
TRIM LEVEL		
Mid ship cleats	~	~
25L water heater 220v with heat exchanger	~	~
40A multi-phase battery charger	~	~
220V shorepower with plugs at chart table, in the galley and cabins	~	~
wood inserts in hull lining of the main saloon	~	~
Shower pump	~	~
Shades for hatches and ports and screens for hatches	~	~
LED navigation lights	~	~
Extra 80Ah battery	~	~
Rigid boom vang	~	~
Shower fixtures and perspex door (version A)	~	~
Additional opening port in the shower compartment (version A)	~	~
Hot and cold cockpit shower		~
Fusion ra205 with bluetooth		~
Cockpit table with central storage compartment, handrail, cup holders		~
Interior and cockpit speakers		~

PERFORMANCE PACKAGE

- Dyneema mainsail and genoa halyards
- Genoa lead rings adjustable from the cockpit
- Spinnaker fittings
- Line bags in cockpit

- Windex 15"
- Additional winches for coachroof with line clutches
- Additional winch handle

EQUIPMENT

ARCHITECTURE

- Hull chine for improved stability and speed
- Long waterline for better speed while sailing and under power
- L-shaped cast iron keel less exposed to seaweed and lines
- High ballast-to-weight ratio
- Balanced rudders with stainless steel shafts

SAILS

Standard

- Horizontally-cut in high-quality dacron
- Semi full-batten mainsail 30.7 m²/330 Sq ft
- Furling Genoa 110% with UV protection 24.6m² / 265 Sq ft

Options

- Lazy bag in Sunbrella® fabric with integrated lazy jacks
- \bullet Performance genoa 110% with UV protection in triradial cut mylar/taffeta 24.6 m² / 265 Sq ft
- Self-tacking jib with UV protection in triradial cut mylar/taffeta laminate 17.9 m² / 193 Sq ft
- Performance square top Mainsail in triradial cut mylar/taffeta 34.1 m²/367 Sq ft
- In mast furling horizontally-cut in high-quality dacron 25.7²/277 Sq ft
- Code 0 in triradial cut mylar/aramid laminate 40.8m²/439 Sq ft, with continuous line furling gear

SAIL HANDLING

Standard

- Genoa winches 2 x Harken 35.2 self-tailing winches for easy use at the helm stations
- Winch handle 1 x Harken handle with ball-be ring grip
- Spinlock jammers
- Mainsheet attached to padeyes forward of companionway hatch with sheet lead back to cockpit winches
- Genoa lead rings

Options

- Self tacking jib ball bearing track on coachroof
- Asymmetrical spinnaker gear : halyard,
 2 sheets, tack line lead forward on deck,
 3 blocks, bowsprit

MAST AND RIGGING

Standard

- Classic mast aluminium with double spreaders, deck-stepped
- Genoa furler with double slot, furling line lead aft to port helm winch
- Running rigging topping lift, mainsail halyard, genoa halyard, mainsheet, genoa sheets in polyester
- Standing rigging discontinuous 1x19 stainless steel wire
- Anchor light and tricolour at masthead, steaming light and bicolour running light on leading edge of the mast

Options

- Furling mast aluminium with double spreaders, deck-stepped
- Double backstay adjustable via a block and tackle system

COCKPIT

Standard

- Cockpit lockers: 2 large lockers in the cockpit floor and a gas locker
- Liferaft locker located in dedicated compartment 80x50x30 cm / 2'7"x1'7"x0'11"
- Teak inlay on cockpit bench seating
- Line lockers at each steering station
- Leather-covered steering wheels with compasses at each steering position
- Swim ladder stainless steel folding ladder mounted on transom step
- Instrumentation dedicated space for instruments within easy reach of helm positions
- Engine controls throttle and engine control panel to starboard, warning lights, ignition

Options

- Large, fold down swim platform with telescopic swim ladder
- Cockpit locker: 1 cockpit locker to port under bench seat
- Solid wood cockpit table with all the same functions of the standard table, but with teak leaves
- Cover for cockpit table in Sunbrella® Taupe
- Teak cockpit floor inlay
- Black, composite steering wheels
- Covers for steering wheels in Sunbrella® Taupe
- Cockpit sprayhood wide Sunbrella® Taupe with vinyl windscreen
- Cockpit bimini Sunbrella® Taupe with stainless steel bows, retractable with storage cover
- Cockpit cushions Sunbrella® Sling Taupe cushions for seating area with attachment clips

DECK HARDWARE

Standard

- Bow pulpit stainless steel
- Stern pulpits stainless steel with buoy bracket and emergency ladder
- Lifelines double level of stainless steel lifelines,
- Toerail
- Cleats 4 x aluminium mooring cleats forward and aft
- Stainless steel handrails on coachroof
- Anchor locker
- Anchor roller single stainless steel fitting
- Fixed windows along coachroof with int grated opening ports
- Fixed hull ports (2) in the saloon
- Opening deck hatches and ports in saloon (2)
- Opening port in starboard aft cabin (1)
- Opening deck hatch in port aft locker (1) (version A)
- Opening deck hatch in port aft cabin (1) (version B)
- Opening port in starboard aft cabin (1)

Options

- Electric windlass 1000W combination rope and 10mm chain
- Opening port in shower (1)
- Mooring kit fenders and docklines
- Bow platform with telescopic, stainless steel access ladder
- Outboard engine bracket mounted on stern pulpit
- Wood rubrail for hull protection
- Lifeline gates
- Anchoring kit Delta anchor 16 kg with 28 meters of 10 mm chain and 40 meters of 18 mm line

LIGHTING

Standard

- Direct and indirect LED lighting in saloon and cabins
- Reading lights in cabins
- Chart light mounted at nav station

ELECTRICAL

Standard

- Electrical panel with 12v breakers, 220v breakers, 12v voltmeter
- 1 12v plug per cabin and at the chart table
- Domestic battery bank capacity, 1 x 80Ah / 12V
- Engine start battery capacity, 1 x 80 A/H 12V
- 12 v alternator output: 125A
- Positive battery switch for engine and domestic bank and general cut-off switch
- Charging distributer and isolator

Options

• Solar panel on coachroof with charging relay

PLUMBING

Standard

FRESH WATER

- Pressurised water distributed through-out the boat via semi-rigid hose
- "Heavy-duty" water pump and accumulator tank for consistent water pressure
- Chromed faucets
- 25 litres hot water tank that is connected to engine heat exchanger and 220v system (finition Premiere)

GREY AND BLACK WATER

- Large manual pump marine toilets
- 80 litre / 12 US Gal holding tank with gravity drain and deck fitting

BILGE

• Manual bilge pump in the cockpit and electric bilge pump with float switch

GAS

Gas detector

ENGINE

Standard

- Engine Yanmar 3YM20 21 HP / 15.3KW - Alternator 125A
- Insulation: foam 40 mm, with fire-retardant film
- Fuel/water separator
- Built-in muffler, air ventilation and stainless steel exhaust fitting
- Stainless steel propeller shaft 25 mm diameter and maintenance free stuffing box
- Fixed 3-blade propeller
- GRP rudders

Options

- Bow thruster with 2 extra batteries, tunnel-mounted
- Folding propeller, 3-blade, Flex-o-Fold



Version A
1 forward cabin, 1 aft cabin, 1 head compartment



Version B
1 forward cabin, 2 aft cabins, 1 head compartment

INTERIOR

Woodwork

- Alpi Teak interior laminated panels with solid wood trim around galley, companionway and cabinetry, finished in satin UV stabilised varnish
- Fully-upholstered hull sides and ceiling
- Light oak laminate floorboards

Option

• Woodwork in Alpi Light Oak with mouldings in solid Alpi Oak, UV stabilised varnish

Saloon

- Saloon with seating, cushions and storage under seating area
- Saloon table with fiddles and removable legs
- Storage cabinets behind seats
- Bar cabinet located in the galley return
- Companionway with hinged door, plexiglass hatch and varnished wood steps

Options

- Deluxe salonn table with folding leaves and bar storage
- Saloon stool, which fits under nav desk to convert portside settee to single berth

Chart table

- Stow-a-way chart table with slate-style finish on work surface and room for a laptop computer
- Full-featured electrical panel with spare breakers, voltmeter and 12v plug

Galley

- L-galley to starboard
- Stainless steel sink with chrome faucet, storage cabinets and drawers
- Gimballed 2-burner stove with protective handrail
- Fridge 100L / 26 US Gal with 12v compressor

Confort

- Cushions in high-density foam
- Premium mattresses

Options

- Air conditioning 220v 16 000 BTU installed under saloon seating. Vents in the saloon and cabins (version A only)
- Microwave 220v stainless steel
- Forced air heating 1 unit 5500 BTU Webasto[®] diesel heater installed in stern, vents in aft cabin, saloon and head compartments
- Foot pump in galley for seawater
- Luxury 2-burner stove with black finish, stainless steel oven/broiler

Forward owner's cabin

- Double berth with high-density foam mattress 2.03x1.70x0.36m/6'7"x5'6"x1'2"
- Storage locker with shelves and hanging bar
- White vinyl lining on hull with lateral wood shelf
- Storage locker under berth
- Wide, bi-fold door for easy access
- Reading light
- Indirect LED lighting

Aft owner's cabin

(version A)

- Double berth with high-density foam mattress 2.00x 1.60m x1.38m/ 6'6" x 5'2"x4'6"
- Hanging locker
- LED ceiling and indirect lights
- · White vinyl lining on hull with lateral wood shelf
- Large head compartment aft with sink, clothes hook, mirror, toilet paper holder, cabinet above sink
- Stainless steel hanging bar for wet clothing
- Sail locker with access from a door in the shower compartment and second access from the cockpit locker

Option

• Single berth in sail locker

Double aft cabin version (version B)

- Double berth with high-density foam mattress (2.00x1.40x1.18m / 6'6"x 4'7"x3'10")
- Hanging locker
- LED ceiling and indirect lights
- White vinyl lining on hull with lateral wood shelf
- Large head compartment aft with sink, clothes hook, mirror, toilet paper holder, cabinet above sink

HEADROOM

Forward cabin	1,92 m / 6'3"	Saloon	1,87 m / 6'1"
Aft cabin(s)	1,91 m / 6'3"	Galley	1,90 m / 6'2"
Companionway	1,88 m /6'2"		



